



## Folding tower frames

### ✓ Professional use

- Available in two widths (0.75m and 1.35m)
- Suitable for the RS5
- All around welded rung-upright connections



## Altrex folding tower frames: All types and sizes available

Altrex folding tower frames are available in two widths (0.75m and 1.35m) in a 3-rungs and 6-rungs model. The bottom side of the folding tower frames are reinforced by a ring, which guarantees the fit. The rungs have an anti-slip profile and have a rung distance of 28 centimetres. All Altrex rungs are welded all around.



### Collar tubes

The collar tubes have caps to prevent fouling. In addition, the collar tubes are flexible, so that the frames fit better.



### Reinforces bottom side

The bottom side of the frames are reinforced by a ring, which guarantees the fit. Furthermore, the locking pins have a transport position and a usage position, so that mounting can be done quickly.



### Available in a multitude of widths

The folding tower frames are available in two different widths. The narrow frame is 0.75m wide and the wide frame is 1.35m wide. In addition, the wide folding tower frame is telescopic adjustable.

## Product specifications

Item number	EAN	Description	series
321000	8711563102262	Frame folding tower single width 3-rung RS TOWER 5	RS TOWER 5
321005	8711563102279	Frame folding tower single width 6-rung RS TOWER 5	RS TOWER 5
322060	8711563108295	Frame folding tower double width telescopic 6-rung RS TOWER 5	RS TOWER 5
326012	8711563204065	Folding unit 6 rung RS 44-POWER	RS TOWER 4
326022	8711563227033	Frame folding tower single width 3-rung	RS TOWER 4